

SPECTRUM COMFORT HEATERS

IR, RFX, & PORTABLE HEATERS

QUALITY | RELIABILITY | LIFE CYCLE ECONOMICS

**HEAT ONE PERSON OR AN ENTIRE BUILDING.
QUIET. QUICK. ECONOMICAL.
WEATHERPROOF.**

Permanent Mount Comfort Heaters

Heat one person or an entire building, Spectrum Industrial Comfort Heaters will do the job quietly, quickly and economically. These attractive heaters are ideal for use in business, commercial and industrial applications. Heaters range from 1KW to 13.5KW of heat output.



Pictured:
Spectrum IR 6kW Heater



Pictured:
Spectrum RFX-3 Heater

IR Heaters

Heat Output: 1.7kW, 2kW, 4.5kW, 6kW or 13.5kW.

Voltage: 120V, 240V or 480V.

Lengths: of 26, 28, 46 or 50 inches.

All parts are replaceable—weld-free construction.

Polished and anodized extruded aluminum reflector.

RFX Heaters

Heat Output: 1kW, 1.5kW, 2kW, 3kW, 4kW, 4.5kW, 6kW, 9kW or 12kW.

Voltage: 240V or 480V.

Lengths: 25, 34, 47, 61 or 73 inches.

Quartz heating elements provide illumination.

Choose reflector pattern to cover a specific area.

Portable Heaters

These tough, durable, weatherproof heaters are designed for inside and outside operation and range from moderate heat output to a heat source with major impact. Great for unheated buildings, thawing equipment and personnel comfort. Applications: Steel Mills, Mining, Railroad, Construction and Loading Docks.

Standard Features

Heat Output: 1.7kW, 2W, 4.5kW, 6KW or 13.5kW.

Polished and anodized extruded aluminum reflector.

Heavy duty metal sheathed elements.

Safety screen and/or safety bars.

Clam shell connection box with open access for cable connection.

Comes equipped with bolt-on dolly, wheel frame, or gripped handle.



Pictured: Spectrum 13.5 kW
Portable Heater

SPECTRUM COMFORT HEATERS

IR, RFX, & PORTABLE HEATERS

Portable Heaters

Part Number	V	kW	Phase	BTU/Hr	Portability	Dimensions
HB-120-1700	120	1.7	1	5800.6414	gripped handle	29.84" x 11.94" x 13.5"
HB-240-2000	240	2	1	6824.284	gripped handle	29.84" x 11.94" x 13.5"
HB-480-2000	480	2	1	6824.284	gripped handle	29.84" x 11.94" x 13.5"
RB-240-4.5	240	4.5	1	15354.639	bolt-on dolly	50.55" x 14.00" x 5.19"
RB-480-4.5	480	4.5	1	15354.639	bolt-on dolly	50.55" x 14.00" x 5.19"
RB-240-6	240	6	3	20472.852	bolt-on dolly	43.28" x 19.28" x 5.63"
RB-480-6	480	6	3	20472.852	bolt-on dolly	43.28" x 19.28" x 5.63"
RB-240-13.5	240	13.5	3	46063.917	welded wheel frame	48.72" x 19.28" x 14.72"
RB-480-13.5	480	13.5	3	46063.917	welded wheel frame	48.72" x 19.28" x 14.72"

IR Permanent Mount Heaters

Part Number	V	kW	Phase	BTU/Hr	# of Elements	Dimensions
IR-120-1700	120	1.7	1	5800.6414	1	26.13" x 10.00" x 6.25"
IR-240-2000	240	2	1	6824.284	1	26.13" x 10.00" x 6.25"
IR-480-2000	480	2	1	6824.284	1	26.13" x 10.00" x 6.25"
IR-240-4500	240	4.5	1	15354.639	1	46.13" x 10.00" x 5.19"
IR-480-4500	480	4.5	1	15354.639	1	46.13" x 10.00" x 5.19"
IR-240-6000	240	6	3	20472.852	3	28.06" x 19.38" x 7.63"
IR-480-6000	480	6	3	20472.852	3	28.06" x 19.38" x 7.63"
IR-240-13500	240	13.5	3	46063.917	3	50.06" x 19.38" x 7.75"
IR-480-13500	480	13.5	3	46063.917	3	50.06" x 19.38" x 7.75"

RFX Permanent Mount Heaters

Part Number	Phase	# of Elements	Dimensions
RFX-1-(V)-(W)-25	1	1	25.00" x 5.56" x 6.38"
RFX-1-(V)-(W)-34	1	1	34.00" x 5.56" x 6.38"
RFX-1-(V)-(W)-47	1	1	47.13" x 5.56" x 6.38"
RFX-1-(V)-(W)-61	1	1	61.00" x 5.56" x 6.38"
RFX-1-(V)-(W)-73	1	1	73.00" x 5.56" x 6.38"
RFX-3-(V)-(W)-25	3	3	25.25" x 5.56" x 18.38"
RFX-3-(V)-(W)-34	3	3	34.25" x 5.56" x 18.38"
RFX-3-(V)-(W)-47	3	3	47.25" x 5.56" x 18.38"
RFX-3-(V)-(W)-61	3	3	61.25" x 5.56" x 18.38"
RFX-3-(V)-(W)-73	3	3	73.25" x 5.56" x 18.38"

To determine a specific part number, replace (V) and (W) with the desired voltage and wattage from those listed in the tables below:

VOLTAGE (V)

RFX-1	240	480
RFX-3	240	480

WATTAGE (W)

RFX-1	1000	1500	2000	3000	4000
RFX-3	3000	4500	6000	9000	12000

Call 800-605-9818 for more information.